

Description of Equipment:

Pantera DP1600i S5 - 1
Alternative drill steel -- Ø60 mm (2⅜") rods / GT60
Alternative drill steel type -- MF-rods
Altitude -- 1000 to 1500 meters above sea level
Drill steel -- LT90 Drill steel For 140-178mm holes
Drill steel length -- 4270 mm (14')
Drill steel type -- MF-rods
Flushing housing -- HL1560T-80
Lowest starting temperature -- Under 0 degrees
Manual languages -- English
Rotation motor -- OMT 800 for 172-178 mm holes

Basic Unit

Rock drill HL 1560T, hydraulic
Cylinder feed LF 1514 HR
Safety cage
Hose reel, drum type
Rod changer RC 1514
Boom ZB 1550 H, telescopic
Carrier FL 6, oscillating
Powerpack, diesel driven, hydraulic pumps and onboard compressor
Hydraulic system, load sensing
Operator's cabin, Ergo Cool with AC
Dust collection system DC 1550 H, hydraulic
Working lights, 15 pcs (9 forward)
Reversing alarm
TIMi for vertical holes and depth measuring
Movable drill steel support
Suction shut down for water holes
Flushing control automatics
EU-safety devices
Gauge set for accumulator pressure checking
1 Set Manuals, paper copy
1 Set Manuals, USB memory

Options

Radio with CD-MP3 player
Reversing camera
Roller blinds for cabin windows
Vacuum cleaner for cabin
Automatic feed alignment for TIMi
TIM3D hole navigation system
LF 1522 feed with hose reel (max starter rod 20 ft)
Thread greasing with 5 gallon bucket
One hole automatic drilling down to preset depth
Anti- freeze system for air lines
Central lubrication system Sandvik
Fast fill connection for engine coolant, hydraulic and engine oils
Fast fill connection for fuel and water tanks (not with option 5110)
Guides for grousers
Hydraulic rear ground support
Towing hook
Led lights 15 pcs.
Fuel powered heater for engine, cabin and water tank
Water injection system

Extra items